

## Mobility Exchange® MX-2800

### DATA SHEET

#### Mobility Exchange MX-2800

Intelligent WLAN Controller for data center deployment. It offers 28 Gbps of switching throughput and supports up to 512 802.11n APs.



**The Mobility Exchange (MX®) family of intelligent WLAN controllers provide the platform for Trapeze Smart Mobile® wireless networks.**

#### Mobility Exchange MX-2800

The Trapeze Mobility Exchange® MX-2800 is the next generation Smart Mobile® WLAN controller for medium to large size enterprise WLAN deployments. It brings unprecedented scalability, manageability, reliability and resiliency features to WLAN networks, mirroring the user experience of wired networks.

Powered by Trapeze's unique hardware-accelerated WLAN processing engine and a high speed security co-processor, the MX-2800 scales to support the most demanding wireless applications indoors and outdoors, including voice over Wi-Fi for thousands of users. It offers 28 Gbps of throughput and supports up to 512 802.11n APs while providing NonStop availability and hitless failover with no service interruption, even in the unlikely event of a controller failure.

Smart Mobile is the only WLAN architecture that offers intelligent switching, which combines both centralized and distributed data forwarding based on the requirements of the underlying application. Operating in conjunction with Trapeze Mobility Point® (MP) access points, and Mobility System Software®(MSS), MX controllers can offload policy enforcement and data forwarding to the MPs, resulting in optimized traffic flow, radically reduced latency, and massive scalability.

The MX-2800 is the latest generation of WLAN controllers from Trapeze Networks. Designed for data center or distributed wiring closet installations, the MX-2800 enables seamless and secure deployment of enterprise class wireless networks over any existing L2/L3 network without disruption.

The MX-2800 combines L2 Ethernet switching, stateful per user and per service firewalls, wireless intrusion protection, 802.1Q trunking and per VLAN spanning tree (PVST+), complete wired to wireless quality of service (QoS), and automated RF management. Clusters of MXs form a Mobility Domain™ which provides seamless roaming, intrusion protection and RF management over large single site wireless LAN deployments. A Network Domain™ interconnects Mobility Domains to support multiple sites and span wide geographic regions with secure, seamless mobility applications and Smart Mobile services.



## Key Features

### Scalability and Reliability

Ports and Interfaces	<ul style="list-style-type: none"> <li>• 8 x GE pluggable SFP and 10/100/1000Base-T RJ45</li> <li>• 2 x 10GE pluggable XFP</li> </ul>
Number of managed Access Points	<ul style="list-style-type: none"> <li>• Up to 512 APs in increments of 64 Access Points licenses</li> </ul>
Network Domain™ service extends the reach of Mobility Domain across a global network	<ul style="list-style-type: none"> <li>• Cluster of 1,024 Mobility Domains, extending mobility across 32,768 MX controllers</li> </ul>
Reliability	<ul style="list-style-type: none"> <li>• Always-on availability and hitless failover with no service interruption for voice and data clients even in the unlikely event of a controller failure</li> <li>• Hot pluggable redundant power supply</li> <li>• Hot pluggable fan tray module</li> <li>• EtherChannel™ load-shared, redundant links</li> <li>• Spanning tree and per-VLAN spanning tree (PVST+)</li> <li>• Resilient network attachment via any MX port</li> <li>• N:1 and N:N redundant MX capabilities</li> </ul>

### Security

Authentication	<ul style="list-style-type: none"> <li>• Supports complete local AAA authentication, including 802.1x, as primary or backup to a centralized AAA server</li> <li>• Supports multiple AAA server groups and can load share across multiple AAA servers or within a server group</li> <li>• Generates and manages X.509 digital certificates</li> <li>• Assigns and enforces per-user authorization policies that are managed centrally from the AAA back-end</li> <li>• Authorizations include virtual private group membership, personal firewall filters, time-of-day/day-of-week access, encryption type, and location-specific policies</li> <li>• IEEE 802.1x with multiple EAP types (TLS, PEAP/MSCHAP, TTLS)</li> <li>• WebAAA, MAC, Open</li> <li>• WiFi WPA2 Enterprise certified</li> </ul>
Encryption Key Management	<ul style="list-style-type: none"> <li>• Encryption distributed in Mobility Point access points</li> <li>• MX generates master and session keys</li> <li>• Provides key management for each encryption technique</li> </ul>
Identity-based Networking	<ul style="list-style-type: none"> <li>• User credentials define access and network resource privileges</li> <li>• Privileges and services follow users as they roam</li> <li>• Maintains a user's membership in the right virtual private group based on the user's authenticated identity</li> <li>• Dynamically enables Virtual Private Groups to support roaming across router boundaries</li> <li>• Centralized management and control</li> </ul>
Endpoint assurance	<ul style="list-style-type: none"> <li>• Trusted Computing Group (TCG) - Trusted Network Connect (TNC) compliant</li> <li>• Microsoft NAP compliant</li> </ul>
Intrusion Detection and Protection	<ul style="list-style-type: none"> <li>• ActiveScan™ rogue and denial-of-service (DoS) attack detection — Scans all bands, associated channels and VLANs, while simultaneously providing wireless connectivity to mobile clients</li> <li>• SentryScan™ — Scans the air continuously on both bands and their associated channel while other MPs support wireless LAN clients</li> <li>• Rogue detection, Intrusion Detection System (IDS) and RF countermeasures</li> <li>• Trapeze/AirDefense integrated Intrusion Detection and Prevention <ul style="list-style-type: none"> <li>- Best in class IDS/IPS</li> <li>- Common Trapeze MP hardware for sensor and service APs</li> <li>- Dynamic threat management- convert MPs to sensors on demand</li> <li>- Threat location and mitigation</li> </ul> </li> </ul>

### Mobility Services

Data Services	<ul style="list-style-type: none"> <li>• Data-intensive applications</li> <li>• Latency-sensitive applications</li> </ul>
Standards-based toll quality voice service	<ul style="list-style-type: none"> <li>• VoIP protocol support</li> <li>• 802.11 e/WMM compliant</li> <li>• Queuing and priority (802.11e/WMM)</li> <li>• Preserve voice priority across network (802.11i PMK cache, WMM)</li> <li>• Bandwidth control for voice (TSPEC)</li> <li>• Maximize handset battery life (U-APSD)</li> <li>• Neighbor report assisted roaming (802.11k)</li> </ul>



Virtual service sets	<ul style="list-style-type: none"> <li>• Multiple SSID support (64 per MP, 32 per radio)</li> <li>• Any mix of crypto and authentication per SSID</li> <li>• Any VLAN topology per SSID</li> <li>• Unique portal page per SSID</li> <li>• Private or shared authentication</li> </ul>
Guest Services	<ul style="list-style-type: none"> <li>• SmartPass™ enables fast and simple configuration for guest access</li> <li>• 64 web portals for customized user group profiles</li> <li>• GuestTunneling to isolate guest traffic across the corporate network</li> </ul>
High speed data services (802.11n)	<ul style="list-style-type: none"> <li>• 802.11n ready</li> <li>• Direct Data Path Forwarding enables local switching of data traffic in the Mobility Point or forwarding of data to Mobility Point upstream or downstream</li> <li>• Mobility Point configured by MX for Direct Data Path Forwarding</li> </ul>
Outdoor services	<ul style="list-style-type: none"> <li>• Wireless backhaul (P-P, P-MP) and Wireless bridging (P-P, P-MP)</li> <li>• Enterprise Ethernet mesh service with Mesh Portal and Mesh Access Point Services with Direct Data Path support</li> <li>• Integrated control and management with indoor Smart Mobile services</li> </ul>
Real time location services	<ul style="list-style-type: none"> <li>• WiFi based active RFID location technology (client and network based)</li> <li>• Integrated with Location appliance</li> </ul>
<b>Management and Control</b>	
Management access	<ul style="list-style-type: none"> <li>• Command Line Interface (SSH v2)</li> <li>• WebView web access (https)</li> <li>• SSL, XML (to RingMaster®)</li> <li>• SNMP v1, v2c, v3</li> </ul>
RF Management	<ul style="list-style-type: none"> <li>• Automated MP Power/channel auto-tuning</li> <li>• Dynamic Frequency Selection (DFS)</li> </ul>
Clustering	<ul style="list-style-type: none"> <li>• An MX cluster is a set of MX controllers that are managed as a single entity - a virtual stack. It allows users to scale easily and configure, monitor and troubleshoot MXs and APs through a single point of entry.</li> </ul>
User management and statistics	<ul style="list-style-type: none"> <li>• Detailed per user per session RF accounting statistics and management</li> <li>• Tracks the location, roaming history, virtual private group, network addresses, state, activity, errors, usage and other attributes by user name, session, VLAN, or user group</li> <li>• Provides per user audit trail and chargeback capability through the accounting component of AAA</li> </ul>
MP management and control	<ul style="list-style-type: none"> <li>• Configures and controls MPs; controls third party APs</li> <li>• The MX is categorized as an access controller (AC) that supports direct, switched, and routed connections</li> <li>• Enables data forwarding in MX or in MP with Smart Mobile technology</li> <li>• Multiple MXs provide resilient control</li> </ul>
Direct Data Path Forwarding	<ul style="list-style-type: none"> <li>• MP configured to switch data traffic locally or forwarded to the MPs downstream or upstream</li> <li>• Optimizes network and MX capacity and performance</li> <li>• Control retained in MX</li> </ul>
Client load balancing	<ul style="list-style-type: none"> <li>• Equalizes the number of client sessions amongst groups of radios that have substantially overlapping coverage areas</li> <li>• Restores equality of numbers of sessions when an AP is added to a group or is brought back up after a transient failure</li> <li>• Allows a balanced group of APs to span multiple MX's in a mobility domain</li> </ul>
Client band steering	<ul style="list-style-type: none"> <li>• Enables client steering across bands for efficient usage of the available spectrum, and reduce network load on the congested 2.4 GHz band</li> </ul>

## Specifications

Hardware Specifications	
Dimensions (W x D x H)	<ul style="list-style-type: none"> <li>• 17.4 in x 18 in x 2.594 in</li> <li>• (44.19 cm x 45.72 cm x 6.58 cm)</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 18 lbs (8.1 kg) with one power supply</li> <li>• 19.5 lbs (8.77 kg) with two power supplies</li> </ul>
Interfaces	<ul style="list-style-type: none"> <li>• 8 x Gigabit Ethernet Small Form-Factor Pluggable (SFP) ports</li> <li>• 8 x Gigabit Ethernet RJ45 ports</li> <li>• 2 x 10 Gigabit Ethernet Small Form-Factor Pluggable (XFP) ports</li> </ul>
Environmental	<ul style="list-style-type: none"> <li>• Operating temperature: 0°C to 50°C</li> <li>• Storage temperature: -40°C to 70°C</li> <li>• Humidity: 10% - 90% (non-condensing)</li> </ul>
Power	<ul style="list-style-type: none"> <li>• 100-240 VAC 50-60 Hz</li> </ul>
Regulatory Safety	<ul style="list-style-type: none"> <li>• UL 609501-1, CB IEC 609501-EN, TUV/GS (EN #s) EN 60950, CSA C22.2 No0, 60950-1-03</li> </ul>
EMI/EMC	<ul style="list-style-type: none"> <li>• FCC Part 15 Class A</li> <li>• ICES Class A</li> <li>• VCCI Class A</li> <li>• EN 55022 Class A</li> <li>• EN 55024</li> <li>• CISPR 22 Class A</li> <li>• Taiwan: CNS 13438 Class A</li> <li>• China: CCC GB 9254-88 Class A</li> <li>• Australia/New Zealand: AS/NZ 3548 Class A</li> </ul>
Supported Standards	
Security and AA RFCs	<ul style="list-style-type: none"> <li>• RFC 2246 Transport Layer Security (TLS)</li> <li>• RFC 2284 EAP</li> <li>• RFC 2315 PKCS #7: Cryptographic Message Syntax Ver 1.5</li> <li>• RFC 2548 Microsoft RADIUS VSAs</li> <li>• RFC 2716 PPP EAPTLS Authentication Protocol</li> <li>• RFC 2759 Microsoft PPP CHAP Extensions, Version 2</li> <li>• RFC 2865 RADIUS Authentication</li> <li>• RFC 2866 RADIUS Accounting</li> <li>• RFC 2869 RADIUS Extensions</li> <li>• RFC 2986 PKCS #10: Certification Request Syntax Ver 1.7</li> <li>• RFC 3580 IEEE 802.1x RADIUS Guidelines</li> </ul>
IEEE Standards	<ul style="list-style-type: none"> <li>• 802.1X: Port Based Network Access Control</li> <li>• 802.3u: 100 BASE-TX Fast Ethernet</li> <li>• 802.3ab: 1000 BASE-TX Gigabit Ethernet</li> <li>• 802.3ae: 10 Gigabit Ethernet</li> <li>• 802.11a/b/g/n, 802.11d, 802.11e, 802.11h, 802.11i, 802.11k</li> </ul>
General	<ul style="list-style-type: none"> <li>• RFC 1122 Host requirements</li> <li>• RFC 1393 Traceroute</li> <li>• RFC 1519 CIDR</li> <li>• RFC 1591 DNS</li> <li>• RFC 2030 SNTP</li> <li>• RFC 768 UDP</li> <li>• RFC 783 TFTP</li> <li>• RFC 791 IP</li> <li>• RFC 792 ICMP</li> <li>• RFC 793 TCP</li> <li>• RFC 826 ARP</li> <li>• IEEE 802.1D Spanning Tree</li> <li>• IEEE 802.1Q VLAN tagging</li> <li>• IEEE 802.3ad (static config)</li> </ul>



---

Management and Control	<ul style="list-style-type: none"><li>• RFC 854 Telnet (server and client)</li><li>• SSHv2 - Secure Shell V2</li><li>• SNMP v1, v2c, v3</li><li>• RFC 1213 MIB-II</li><li>• RFC 1866 HTML</li><li>• RFC 2068 HTTP</li><li>• RFC 3164 Syslog</li><li>• Trapeze private MIB</li></ul>
IP Multicast	<ul style="list-style-type: none"><li>• RFC 1112 IGMP v1</li><li>• RFC 2236 IGMP v2</li></ul>
Quality of Service (QoS)	<ul style="list-style-type: none"><li>• 802.11e, Wi-Fi Multimedia (WMM)</li><li>• SpectraLink Voice Priority (SVP)</li><li>• RFC 2472 DiffServ precedence</li><li>• RFC 2597 DiffServ Assured Forwarding</li><li>• RFC 2598 DiffServ Expedited Forwarding</li></ul>

---

## Ordering Information

---

MX-2800-xx	<ul style="list-style-type: none"><li>• MX-2800 with two 10 GbE XFP ports and 8 x 1000Base-T (RJ-45 and SFP) ports, including 64 MP license, single PSU.</li></ul>
MX-2800-U64	<ul style="list-style-type: none"><li>• 64 MP license upgrade for MX-2800 (max. 512 MPs)</li></ul>
MX-2800-PSU-xx	<ul style="list-style-type: none"><li>• PSU for MX-2800 redundant power or spare</li></ul>

---